

**ELETRAS** S.R.L.

since 1978

ST SERIES

VOLTAGE STABILISERS

POWER: from 1.000 to 450.000VA

Input voltages: 230/400 VAC

Output voltages: +/- 15%

Output stabilisation: +/- 1%

ON DEMAND:

Customised input / output voltages

Customised output stabilisation

TECHNICAL DATA:

Continuous service

Protection degree: IP00



Code	Input (VAC)		Power (KVA)	Power (KVA)	Dimensions in mm			Weight (Kg)	Phase setting
			+/-15%	+/-20%	Length L	Depth P	Height H		
STM01	Single-phase	230	1,2	0,8	300	300	240	16	
STM02	Single-phase	230	2	1,5	300	300	240	19	
STM04	Single-phase	230	4	3	300	300	240	22	
STM06	Single-phase	230	6	4,5	300	300	240	26	
STM10	Single-phase	230	10	7,5	300	520	240	36	
STM15	Single-phase	230	15	11	300	520	240	44	
STM20	Single-phase	230	20	15	300	520	500	85	
STM25	Single-phase	230	25	20	600	300	830	105	
STM30	Single-phase	230	30	25	600	300	830	135	
STM40	Single-phase	230	40	30	600	400	1100	185	
STM50	Single-phase	230	50	40	600	400	1100	225	
STT003A	Three-phase	400	3	2,5	300	500	520	55	Average
STT006A	Three-phase	400	6	4,5	300	500	520	60	Average
STT012A	Three-phase	400	12	9	300	500	520	70	Average
STT018A	Three-phase	400	18	13	600	300	870	85	Average
STT024A	Three-phase	400	24	18	600	300	870	110	Average
STT030A	Three-phase	400	30	22	600	300	870	130	Average
STT040A	Three-phase	400	40	30	600	400	1100	145	Average
STT050A	Three-phase	400	50	36	600	400	1100	160	Average
STT060A	Three-phase	400	60	45	600	400	1100	210	Average
STT075A	Three-phase	400	75	60	800	500	1500	270	Average
STT100A	Three-phase	400	100	75	800	500	1500	410	Average
STT135A	Three-phase	400	135	----	1000	500	1500	540	Average
STT150A	Three-phase	400	150	----	1200	500	1500	650	Average
STT175A	Three-phase	400	175	----	1200	500	1500	720	Average
STT230A	Three-phase	400	230	----	1200	500	1500	810	Average
STT003I	Three-phase	400	3	2,5	300	500	520	62	Independent
STT006I	Three-phase	400	6	4,5	300	500	520	67	Independent
STT012I	Three-phase	400	12	9	300	500	520	77	Independent
STT018I	Three-phase	400	18	13	600	300	870	92	Independent
STT024I	Three-phase	400	24	18	600	300	870	120	Independent
STT030I	Three-phase	400	30	22	600	300	870	140	Independent
STT040I	Three-phase	400	40	30	600	400	1100	165	Independent
STT050I	Three-phase	400	50	36	600	400	1100	180	Independent
STT060I	Three-phase	400	60	45	600	400	1100	230	Independent
STT075I	Three-phase	400	75	60	800	500	1500	300	Independent
STT100I	Three-phase	400	100	75	800	500	1500	430	Independent
STT135I	Three-phase	400	135	----	1000	500	1500	570	Independent
STT150I	Three-phase	400	150	----	1200	500	1500	680	Independent
STT175I	Three-phase	400	175	----	1200	500	1500	750	Independent
STT230I	Three-phase	400	230	----	1200	500	1500	850	Independent